

Pneumatically Operated Valve DN 8 - 20 mm (3/8" - 3/4")



Cf. 1, 2 & 3

Features

- Efficient thermoplastic piston actuator with stainless steel distance piece
- Control air connection 90° to flow direction
- Flexible diaphragm suspension
- Encapsulated diaphragm
- Optical indicator
- Compact design, the outside diameter of the actuator is the same size as the bonnet flange

Optional

- Available with a wide range of control equipment and accessories see page 57 to 62, also for retrofitting
- Control air connection in flow direction

Technical Data

Control function (Cf.):	Pneumatically operated Normally closed (NC): Cf. 1 & 4 Normally open (NO): Cf. 2 & 5 Double acting (DA): Cf. 3
Direction	
Control connection:	At Cf. 1, 2 & 3, 90° to flow direction, standard At Cf. 4 & 5 in flow direction
Max. working pressure:	Unidirectional (delta p = 100%) EPDM diaphragm 8 bar (120 psi) PTFE diaphragm 7 bar (100 psi)
Higher working pressure may be achieved with different actuator. Please contact us for working pressure above the indicated maximum.	
Max. working temperature:	160°C (320°F) dependent on application
Control pressure:	Cf. 1 & 4 4 - 7 bar (60 - 100 psi) Cf. 2, 3 & 5 4 - 5 bar (60 - 70 psi)
Diaphragm material:	EPDM or PTFE
Valve body material:	Forged 1.4435/ 316 L ASME/BPE Investment cast 1.4435/ 316 L Other alloys
End connection:	Butt weld ends see fold out page 13 Clamps and flanges see page 14 and 15 Special ends
Actuators suitable for:	Two-Way bodies Welded configurations T-bodies Multiport bodies Tank bottom bodies
Flow rate:	Kv in m ³ /h (Cv in GPM) see page 7
Diaphragm size:	MA 10 all sizes

Butt weld ends
MA 10
Fold out page 13

